

An adiabatic mode time-dependent parabolic equation

M.Yu. Trofimov

Il'ichev Pacific oceanological institute, Baltiyskay St. 43, Vladivostok, 41, 690041, Russia

Abstract

An adiabatic mode time-dependent parabolic equation for the 3D problems of underwater acoustic propagation problem is derived by the multiple-scale method. The Cauchy problem for this equation is considered.

Key words: parabolic equation, adiabatic mode

PACS: 43.30.+m,

PACS: 43.20.Bi

1 Introduction

An adiabatic mode continuous wave parabolic equation was derived by the factorization of horizontal Helmholtz operator in the recent paper of M. Collins [1]. Another form of this equation was obtained by the generalized multiple-scale method in our paper [2]. The use of multiple-scale method is especially important in nonstationary problems because it automatically gives the correct variables for the amplitude and phase of the acoustic field [3].

In this paper we derive by the multiple-scale method an adiabatic mode time-dependent parabolic equation and the characteristic equations for the associated Hamilton-Jacobi equation. We use the characteristic variables to give a reduction of the Cauchy problem for the derived equation to a family of those for (formally) continuous wave parabolic equation.

Email address: trofimov@poi.dvo.ru (M.Yu. Trofimov).

2 Formulation and derivation

We start with the acoustic wave equation for nonstationary media

$$\operatorname{div} \left(\frac{1}{\rho} \operatorname{grad} p \right) - \frac{\partial}{\partial t} \left(\frac{1}{\rho} n^2 \frac{\partial p}{\partial t} \right) = 0, \quad (1)$$

where p is the acoustic pressure, ρ is the density, $n = 1/c$ is the index of refraction, c is the sound speed. The variables are nondimensional, based on a length scale $\bar{l}$, a time scale $\bar{l}/\bar{c}$ (where $\bar{c}$ is a typical value of sound speed), and a density scale $\bar{\rho}$ (a typical value of the density). Equation (1) is considered in a domain $-H \leq z \leq h(x, y, t)$, where H is the depth of a fictitious boundary in the bottom bed, with the boundary conditions

$$p = 0 \quad \text{at} \quad z = h(x, y, t), \quad \frac{\partial p}{\partial z} = 0 \quad \text{at} \quad z = -H. \quad (2)$$

We suppose that the density and the index of refraction are piece-wise continuous with respect to z with discontinuities at surfaces $z = h^{(l)}(x, y, t)$, $l = 1, \dots, N$. The typical examples of such surfaces are the ocean bottom and the seismic boundaries in it. At these surfaces we set the interface boundary condition

$$p_+ = p_-, \quad \left(\frac{1}{\rho} \frac{\partial p}{\partial \nu} \right)_+ = \left(\frac{1}{\rho} \frac{\partial p}{\partial \nu} \right)_-, \quad (3)$$

where $\partial/\partial \nu$ denotes the normal derivative. By the subscripts “+” and “−” are marked the limits of variables from above and below the surface.

Let ϵ be a small parameter. We introduce the slow variables $T = \epsilon t$, $X = \epsilon x$, $Y = \epsilon^{1/2} y$, the fast variable $\eta = (1/\epsilon)\theta(X, Y, z, T)$, and postulate the expansions

$$\begin{aligned} \rho &= \rho_0(X, T, z) + \epsilon \rho_1(X, Y, T, z), \\ n &= n_0(X, T, z) + \epsilon n_1(X, Y, T, z), \\ h &= \epsilon h_1(X, Y, T), \\ h^{(l)} &= h_0^{(l)}(X, T) + \epsilon h_1^{(l)}(X, Y, T), \quad l = 1, \dots, N, \\ p &= p_0(X, Y, T, z, \eta) + \epsilon p_1(X, Y, T, z, \eta) + \dots \end{aligned}$$

Substituting these expansions to the (1), (2) and (3) and replacing partial derivatives by the rule

$$\frac{\partial}{\partial X} \rightarrow \frac{\partial}{\partial X} + \frac{1}{\epsilon} \theta_X \frac{\partial}{\partial \eta},$$

and analogously for the variables z , Y and T , we obtain by collecting terms of the same order of ϵ a sequence of boundary value problems.

The problems at $O(\epsilon^{-2})$ and $O(\epsilon^{-1})$ show that θ is independent from z and Y .

At $O(\epsilon^0)$ we obtain

$$\frac{1}{\rho_0} (\theta_X)^2 p_{0\eta\eta} + \left(\frac{1}{\rho_0} p_{0z} \right)_z - \frac{1}{\rho_0} n_0^2 (\theta_T)^2 p_{0\eta\eta} = 0.$$

The separation of variables η and z leads, up to the gauge transformation of the phase θ , to a solution of the form

$$p_0 = A(X, Y, T) \phi(z, X, T) e^{i\eta}.$$

The function ϕ is a solution to the spectral boundary value problem

$$\left(\frac{1}{\rho_0} \phi_z \right)_z + \frac{1}{\rho_0} n_0^2 \omega^2 \phi = \frac{1}{\rho_0} k^2 \phi \quad (4)$$

with the boundary conditions

$$\phi = 0 \quad \text{at} \quad z = 0$$

$$\phi_z = 0 \quad \text{at} \quad z = -H$$

and the interface conditions

$$\phi_+ = \phi_-, \quad \left(\rho_0^{-1} \partial \phi / \partial z \right)_+ = \left(\rho_0^{-1} \partial \phi / \partial z \right)_- \quad \text{at} \quad z = h_0^{(l)}, \quad l = 1, \dots, N.$$

Here $k = \theta_X$ is the local wave number and $\omega = -\theta_T$ is the local frequency, the spectral parameter of (4) is identified with k^2 . The problem (4) can be considered as the Hamilton-Jacobi equation:

$$(\theta_X)^2 = \mathcal{F}^2(\theta_T, X, T). \quad (5)$$

The phase θ can be complex with $\text{Im} \theta \geq 0$ (the dissipation condition), so for the normalization and orthogonality conditions we use the non-Hermitian inner product

$$(\phi, \psi) = \int_{-H}^0 \frac{1}{\rho_0} \phi \bar{\psi} dz. \quad (6)$$

which accords with the biorthogonality conditions [4]

The consideration of the solvability condition of the boundary value problem at $O(\epsilon)$, formulated as the orthogonality condition with respect to (6), gives the parabolic equation

$$A_X + \frac{1}{c_g} A_T - i \frac{1}{2k} A_{YY} + \alpha A = 0, \quad (7)$$

where

$$\begin{aligned}
\alpha = & \frac{1}{2} (\ln k)_X + \frac{1}{2} (\ln k)_T \cdot \frac{1}{c_g} + \frac{1}{2} \left(\frac{1}{c_g} \right)_T \\
& - i \frac{1}{2k} \int_{-H}^0 \frac{\rho_1}{\rho_0^2} [(\phi_z)^2 + k^2 \phi^2 - \omega^2 n_0^2 \phi^2] dz \\
& - i \frac{\omega^2}{k} \int_{-H}^0 \frac{n_1}{\rho_0} n_0 \phi^2 dz - \frac{i}{2k \rho_0} h_1 \cdot (\phi_z)^2 \Big|_{z=0} \\
& + \frac{i}{2k} \sum_{l=1}^N \left(\frac{1}{\rho_0} \phi_z \right)_+^2 \cdot h_1^{(l)} \cdot (\rho_{0+} - \rho_{0-}) \Big|_{z=h_0^{(l)}} \\
& - \frac{i}{2k} \sum_{l=1}^N h_1^{(l)} \phi^2 \left[k^2 \left(\frac{1}{\rho_{0+}} - \frac{1}{\rho_{0-}} \right) - \right. \\
& \quad \left. \omega^2 \left(\frac{n_{0+}^2}{\rho_{0+}} - \frac{n_{0-}^2}{\rho_{0-}} \right) \right] \Big|_{z=h_0^{(l)}} ,
\end{aligned}$$

c_g is the group velocity of the normal mode under consideration.

For the waves propagating to the positive X -direction the Hamilton-Jacobi equation (5) takes the form

$$\theta_X = \mathcal{F}(\theta_T, X, T) . \quad (8)$$

3 The Cauchy problem

For equations (8), (7) we consider the Cauchy problem with the initial conditions $\theta(X=0, T) = \theta_0(T)$, $A(X=0, Y, T) = A_0(Y, T)$. For equation (8) the solution of this problem is given by the method of characteristics

$$\theta(X, T(X)) = \theta_0(\tau) + \int_0^X \left(k - \frac{\omega}{c_g} \right) ds ,$$

where $(T(s), \omega(s))$ is a solution of the characteristic system

$$\begin{aligned}
\frac{d\omega}{ds} &= -\mathcal{F}_T , \\
\frac{dT}{ds} &= \mathcal{F}_\omega = \frac{1}{c_g} ,
\end{aligned}$$

with initial conditions $T(0) = \tau$, $\omega(0) = -\theta_T(0)$. The expression for the group velocity is well known:

$$c_g = \left(\frac{\omega}{k} \int_{-H}^0 \frac{n_0^2}{\rho_0} \phi^2 dz \right)^{-1} .$$

The expression for $\mathcal{F}_T$ is given by the formula

$$\begin{aligned}\mathcal{F}_T = & \frac{1}{2k} \int_{-H}^0 \frac{1}{\rho_0^2} \phi^2 \left[\left(\omega^2 n_0^2 \right)_T \rho_0 + k^2 \rho_{0T} - \omega^2 n_0^2 \rho_{0T} \right] dz \\ & + \frac{1}{2k} \int_{-H}^0 \frac{\rho_{0T}}{\rho_0^2} (\phi_z)^2 dz \\ & - \frac{1}{2k} \sum_{l=1}^N \left(\frac{1}{\rho_0} \phi_z \right)_+^2 \cdot h_{0T}^{(l)} \cdot (\rho_{0+} - \rho_{0-}) \Big|_{z=h_0^{(l)}} \\ & + \frac{1}{2k} \sum_{l=1}^N h_{0T}^{(l)} \phi^2 \left[k^2 \left(\frac{1}{\rho_{0+}} - \frac{1}{\rho_{0-}} \right) \right. \\ & \quad \left. - \omega^2 \left(\frac{n_{0+}^2}{\rho_{0+}} - \frac{n_{0-}^2}{\rho_{0-}} \right) \right] \Big|_{z=h_0^{(l)}}.\end{aligned}$$

The Cauchy problem for equation (7) can be solved by passing to the characteristic variables s , τ . In these variables equation (7) has a more simple form

$$A_s - i \frac{1}{2k} A_{YY} + \alpha A = 0.$$

The solution in initial variables is recovered then as $A(X, T) = A(s, \tau)$ at $s = X$, where $T = T(X)$ is a solution of the characteristic system with the initial condition $T(0) = \tau$. Here τ is simply a parameter, so we have formally a family of Cauchy problems for the continuous wave form of adiabatic mode parabolic equation (the expression for the coefficient is, of course, different), which was considered in details in [2].

4 Conclusion

In this paper the derivation of the new adiabatic mode parabolic equation (7) is outlined and the explicit expressions for its coefficients are given. The Cauchy problem for this equation is proposed to solve by passing to the characteristic variables and for the corresponding characteristic system the explicit expressions for its coefficients are given.

References

- [1] *Collins M. D.* 1993 The adiabatic mode parabolic equation. J. Acoust. Soc. Amer. 94(4): 2269-2278.

- [2] *Trofimov M. Yu.* 1999. Narrow-angle parabolic equations of adiabatic single-mode propagation in horizontally inhomogeneous shallow sea. *Acoustical Physics* 45(5): 575-580.
- [3] *Trofimov M. Yu.* 2000. Time-dependent parabolic equations for two-dimensional waveguides. *Technical Physics Letters* 26(9): 797-798.
- [4] *Coddington E.A., Levinson N.*, Theory of ordinary differential equations. N.-Y. et al.: McGraw-Hill, 1955.